

<div><div><div><div><div></div><div>Nissan Qashqai</div></div></div><div><div>Installation Process</div><div>Electric tail gate lift system</div><div>TL105-5829</div></div></div><div></div><div>NO:5658291010000</div></div>	<div><div>NOTE</div><div>Installation Precautions of Electric Tail gate Lifts</div><div>1.To ensure safety and normal usage of our products, please let the professional sales staff to install; to avoid damaging the machine or causing accidents, please do not dismantle the products.</div><div>2.To start the engine before installation, check the car dashboard display function, whether the buttons operate normally, whether there is any scratches on car interior and surface. If any problems, reflect to the customer immediately.</div><div>3.Check whether the tailgate can normally open and close or not, check if there is any problem with the lights.</div><div>4.Turn off the engine, prepare tools.</div><div>5.For installation personnel: please remove metal objects and any other hard objects to prevent car damage during the installation process.</div><div>6.Remove automotive components and place them carefully to avoid scratching the dashboard; wiring debris need to be tidied up in time, do not leave them in the car; Joints must be well insulated to prevent short circuits.</div><div>7.According to our wiring way, to avoid affect the car moving parts, such as steering column, the accelerator and brake pedals, etc., each harness should be fixed after wiring, to avoid getting loose.</div><div>8.Connect each harness according to our wiring way(pay attention to the position of ground wire).</div><div>9.Do not change the wires or accessories with the power on.</div><div>▲After installation, close the tail gate manually, so that the system can initialize.</div></div>	<div><div>Wire Description</div><div><div><div>A.To connect control box port①</div><div>B.To connect tailgate lock port(in)</div><div>C.To connect tailgate lock port(out)</div><div>D.To connect original tailgate button(out)</div><div>E.To connect original tailgate button(in)</div></div><div><div>A.Joint to canbus</div><div>B.Front button port</div><div>C.Joint to power cable C</div><div>D.Joint to communication C</div></div><div><div>A.Communication C</div><div>B.OBD(in)</div><div>C.OBD(out)</div></div><div><div>A.Back button port</div><div>B.Control box port③</div><div>C.Buzzer D</div></div><div><div>To connect front button plug of canbus switch cable</div></div><div>▲All above is subject to change without prior notice. All rights reserved.</div></div></div>	<div><div>Wire Description</div><div><div>To connect control box port②③</div><div>To connect control box port③</div><div><div>Connect to the added back button wire C</div><div><div>A.Ground cable</div><div>B.Joint to power cable D</div><div>C.Fuse</div><div>D.Power cable clamp</div><div><div>A.Control box port⑤</div><div>B.Control box port⑥</div><div>C.Connect to CANBUS C</div><div>D.Connect to power pickerB</div><div><div>Control box backseat(front)</div><div>Control box backseat(back)</div></div></div></div></div></div></div>	<div><div>Installation Steps</div><div>1.Nissan Qashqai</div><div>2.Dismantle the buckle and screw in the circle as shown as shown in the picture, the left and right side are the same.</div><div>3.Pry the plaque and take it down.</div><div>4.after dismantling the tailgate plaque.</div><div>5.Dismantle the crashproof plastic card on the tailgate.</div><div>6.Pull out the crashproof plastic, dismantle the crashproof plastic seat.</div><div>7.Pull out the crashproof plastic, dismantle the crashproof plastic seat.</div><div>8.Pry the circlip of original gas spring,take down the gas spring (the left and right side are the same)</div></div>	<div><div>Installation Steps</div><div>9.Take down the original bodywork bulb screw,(the left and right side are the same)</div><div>10.Fix our bracket on the bodywork.(Make the bottom of bracket set close to the rain guide groove,the left and right side are the same)</div><div>11.Use fingers to fix the screw of our tailgate bracket,place the nut slice into the square hole of tailgate.</div><div>12.Check the screw hole,put your hand into the iron sandwich of tailgate to fix the nut slice,tighten the screw.</div><div>13.Then tighten another screw,fix the bracket,(the left and right side are the same)</div><div>14.Install our pole.</div><div>15.Drill a hole at the position where the motor cable goes,go through the motor cable.</div><div>16.Pull out the plaque,you can see the OBD plug.</div></div>	<div><div>Installation Steps</div><div>17.After pulling out the plaque.</div><div>18.Use a crow plate to dismantle the left side cover of driver's room.</div><div>19.Take down two screws.</div><div>20.Take down the left plaque of steering wheel.</div><div>21.Use a crow plate to pry up the right corner plaque of steering wheel,then use hand to lift up the lower part,take down the whole plaque.</div><div>22.Effect of after taking down.</div><div>23.Unscrew 3 screws,pull out the whole original button group.</div><div>24.Take down the spare button of the button group,install our front button, then connect the cable.</div></div>	<div><div>Installation Steps</div><div>25.Pick power as shown in the picture</div><div>26.Position of ground cable.</div><div>27.Make the power cable go through along the plaque of left door.</div><div>28.Lay the power cable along the direction of the arrow.</div><div>29.Make the power cable and latch cable go through the water pipe of tailgate.</div><div>30.Make the power cable and latch cable go through along the left tailgate.</div><div>31.Fix the control box at this position.</div><div>32.Original button plug.(Note:the plug is on the left of tailgate,avoid to confuse the other plug)</div></div>	<div><div>Installation Steps</div><div>33.Disconnect the original button plug, joint to our button plug.</div><div>34.Disconnect the original lock plug, joint to our lock plug.</div><div>35.Drill a hole on the plaque of tailgate, install the back button.</div><div>36.Join the cables to the control box.</div><div>37.Paste protective film on the tail gate as shown,both sides</div><div>▲Remote operative mode of the original car:Press on the unlock button 3 times</div></div>